

STM Truck Mounted Forklifts



The Sellick STM transportable forklift provides rugged reliability and service. Complete with a powerful 56 hp Tier 4 compliant diesel engine, it's a complete delivery system as the driver can unload, place and reload the STM and its cargo in minutes directly at the job-site. Add the versatility of a new 4-way multi-directional model and supplies can be transported sideways where space is limited. All STM's feature a side-mount operator platform that provides excellent ergonomics and ensures complete 360° visibility for the operator.

Model	Capacity (Type)
STM55	5,500 lbs
STM70	7,000 lbs
STM55P	5,500 lbs (Pantograph)
STM55-4W	5,500 lbs (4-Way)
STM55P-4W	5,500 lbs (4-Way w/ Panto.)

The STM55P maximizes productivity by allowing operators to safely load and



unload cargo from one side of a truck and eliminates the need to turn the truck around to unload the other side.

This lightweight and versatile forklift also enables sod growers, nurseries and building supply yards to pickup and deliver in muddy, rough terrain conditions. Large standard 31 x 15.5 - 10 tires provide excellent traction in any condition.



Sellick forklifts are backed by a national distribution network for parts and service offering prompt and personal service whenever you need it.



STM Truck Mounted Forklifts

STM Specifications	STM55	STM55P	STM70	STM55-4W	STM55P-4W
Lift capacity @ 24" lift centre	5,500 lbs / 2,500 kg	5,500 lbs / 2,500 kg	7,000 lbs / 3,175 kg	5,500 lbs / 2,500 kg	5,500 lbs / 2,500 kg
Base Operating Weight	6,450 lbs / 2,926 kg	7,650 lbs / 3,470 kg	7,050 lbs / 3,198 kg	8,285 lbs / 3,758 kg	9,475 lbs / 4,298 kg
Overall length (without forks)	102" / 2,591 mm	105.5" / 2,680 mm		99" / 2,515 mm	107" / 2,718 mm
Overhang length	63" / 1,600 mm	73" / 1,829 mm	67" / 1,702 mm	62" / 813 mm	70" / 1,778 mm
Masts Available	96" / 2,440 mm		96" / 2,440 mm		
	120" / 3,050 mm				
	144" / 3,660 mm				
Mast tilt forward	12°				
Mast tilt rearward	10°	8°	10°	8°	
Frame opening	60" / 1,524 mm			58" / 1,473 mm	
<i>Because of our constant dedication to product improvement, all specifications are subject to change without notice</i>					

Standard Functional Features

- Kohler KDI1903TCR Tier 4 compliant, turbo-charged 56 HP diesel engine
- Fuel/water separator
- Stabilizers
- ROPS/FOPS/Operators Platform
- Engine controls and gauges
- Hydrostatic steering
- Transport tie down chains
- 3-wheel drive
- Traction lock
- 5-spool hydraulic valve
- Sideshifting mast
- Dual element air filter
- Inching control
- Hydraulic parking brake
- Lights, horn
- Fully adjustable seat with retractable seatbelt
- Hydrostatic drive with anti-stall
- Backup alarm
- Remote hydraulic pressure release for mounting

Optional Equipment

- Strobe light
- Wide range of forks
- Block/oil pan heater
- Cold weather packages
- Tilt Steering
- Load backrest
- Truck or trailer mounting packages
- Custom paint
- Variety of tire options
- Rear view mirrors
- Suspension Seat
- Fork positioner